

Product Description and Application

Mobil ATF is an extra high performance automatic transmission fluid exceeding the latest revised specifications of Ford Mercon® and General Motors, Dexron® III Specifications.

Mobil ATF is recommended for most passenger car and commercial automatic transmissions. It is also suitable for power steering systems, hydraulic applications and some manual transmissions where an automatic transmission fluid is specified.

Benefits

Mobil ATF offers the following benefits:

- The correct frictional requirements to give smooth transmission operation over wide operational bands
- Protection against degradation at high operating temperature and extended service
- Low temperature pumpability and circulation ensuring cold start performance
- Compatibility with all conventional seal materials found in transmission units

Specifications

Mobil ATF is approved to or meets the following specifications and builder service fill requirements:

- Allison C4 (C4-19321894)
- Ford Mercon® (M-931220)
- General Motors Dexron® III (G-34064)
- MAN 339-F (TUC 3644/96)
- Mercedes Benz 236.1/236.5
- Nissan genuine ATF, Matic Fluid D
- Voith G607
- ZF TE-ML-09 Power and Hydrostatic steering gearboxes in passenger cars
- ZF TE-ML-14 Ecomat torque converters in heavy duty vehicles

Health and Safety

Based on available toxicological information, it has been determined that this product poses no significant health risk when used and handled properly.

Details on handling, as well as health and safety information, can be found in the Material Safety Data Bulletin which can be obtained through Mobil Oil Company Ltd., by telephoning 01372 22 2000.

Typical physical characteristics are given in the table. These are intended as a guide to industry and are not necessarily manufacturing or marketing specifications.

Typical Characteristics

	Mobil ATF
Viscosity, cSt at 40°C	35
Viscosity, cSt at 100°C	7.9
Viscosity Index	211
Pour Point, °C	-48
Flash Point, °C	196
Colour, ASTM D1500	Red

Due to continual product research and development, the information contained herein is subject to change without notice.

Mobil Oil Company Limited
Acting as Agent for Mobil Lubricants UK Limited
ExxonMobil House, Ermyn Way
Leatherhead, Surrey, KT22 8UX
Telephone: 01372 22 2000

