

Product Data Sheet

Cutrex 411
Honing and Finishing Oil

Product Description

Cutrex 411 is a premium quality multi purpose neat cutting oil. It contains a high quality mineral oil and high performance additives.

Benefits

- Clear and transparent for easy visibility of workpiece
- Excellent lubrication properties despite low viscosity
- Allows optimal surface finish and tolerances
- High flash point for low evaporation

Application

Cutrex 411 is particularly suitable for precision machining operations or finishing. It can also be used for high performance honing.

Health and Safety

Based on available toxicological information, these products produce no adverse effects on health when properly handled and used. No special precautions are suggested beyond attention to good personal hygiene, including laundering oil-soaked clothing and washing skin contact areas with soap and water. Additional health & safety information on these products, including Material Safety Data Bulletins, are available on request from your local Mobil company.

Typical Characteristics

Cutrex 411

	Test Method	Units	
Appearance			clear
Colour			amber
Density at 15°C	ISO3675	g/cm ³	0.848
Kinematic Viscosity at 20°C	ISO3106	mm ² /s	10
Kinematic Viscosity at 40°C			5.4
Flash Point (COC)	ISO2719	°C	110
Copper Corrosion	ISO2160		1A

Due to continual product research and development, the information contained herein is subject to change without notice

Mobil Oil Company Limited
Acting as Agent for Mobil Lubricants UK Limited
ExxonMobil House, Ermyn Way
Leatherhead, Surrey, KT22 8UX
Telephone: 01372 22 2000

