

Product Data Sheet

Mobil Extra 2T Semi-Synthetic Two-stroke Motorcycle Oil

Product Description and Application

Mobil Extra 2T is a superior semi-synthetic lubricant recommended for all on and off road two-stroke machines. Its semi-synthetic base and carefully selected additive package ensures the highest standard of lubrication in all two-stroke engine applications.

Benefits

Mobil Extra 2T offers the following benefits:

- Considerably reduces all engine and exhaust deposits
- Protects against corrosion
- Eliminates plug fouling
- Minimises exhaust smoke
- Particularly recommended for town riding
- Recommended mixture strength 3% - 4% (5% during running in period)
- Specially selected diluent ensures complete mixing with the fuel and avoids separation after standing

Specifications

Mobil Extra 2T exceeds the API TC specification (previously TSC3)

Health and Safety

Based on available toxicological information, it has been determined that this product poses no significant health risk when used and handled properly.

Details on handling, as well as health and safety information, can be found in the Material Safety Data Bulletin which can be obtained through Mobil Oil Company Ltd., by telephoning 01372 22 2000.

Typical physical characteristics are given in the table. These are intended as a guide to industry and are not necessarily manufacturing or marketing specifications.

Typical Characteristics

Mobil Extra 2T

Relative Density 15 °C/4 °C	0.87
Viscosity, cSt at 40°C	66
Viscosity, cSt at 100°C	9.4
Viscosity Index	121
Pour Point, °C	-27 max.
Flash Point, COC °C	150 min.
Total Base Number, mg KOH/g	2.6
Colour	4.5

Due to continual product research and development, the information contained herein is subject to change without notice.

Mobil Oil Company Limited
Acting as Agent for Mobil Lubricants UK Limited
ExxonMobil House, Ermyn Way
Leatherhead, Surrey, KT22 8UX
Telephone: 01372 22 2000

