

Mobilube HD 80W-90, 85W-140

Heavy Duty Automotive Gear Lubricants

Product Description

Mobilube HD 80W-90 and 85W-140 are high performance, heavy duty gear lubricants formulated from high performance base oils and an advanced additive system. These lubricants are engineered for automotive applications including heavy duty axles and final drives where extreme pressures and shock loading are expected. They provide excellent performance where API GL-5 service is required.

Features & Benefits

Today's heavy equipment applications place higher performance demands on drive train lubricants. Higher speeds, higher torque, and heavier loads require improved formulations to maximise equipment life and optimise operating costs. Longer service intervals place additional demands on the gear lubricant requiring effective basestock and additive systems. Mobilube HD Series of gear lubricants are engineered to meet these challenges. The key benefits include:

Features	Advantages and Potential Benefits
Exceptional thermal stability and resistance to high temperature oxidation	Extended gear and bearing life due to minimal deposits Longer seal life
Outstanding protection against low speed/high torque wear and against high speed scoring	Increased load carrying capability Reduced maintenance costs and longer equipment life
Excellent rust and corrosion protection	Reduced wear and longer component life
Effective low temperature lubrication	Improved startability
Compatible with typical automotive seals and gaskets	Minimum leakage and reduced contamination

Applications

- Heavy duty axles and final drives requiring API GL-5 level performance
- Passenger cars, on highway light and heavy duty trucks and commercial vehicles
- Off highway industries including: construction, mining, quarrying, and agriculture
- Other heavy duty industrial and automotive applications involving hypoid gears operating under conditions where high speed/shock load, high speed/low torque, and/or low speed/high torque prevail

Specifications & Approvals

Mobilube HD Gear Oils meet or exceed the following industry specification:	80W-90	85W-140
API GL-5	X	X

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.



Typical Properties

Mobilube HD Properties	80W-90	85W-140
SAE Grade	80W-90	85W-140
Viscosity, ASTM D 445		
cSt @ 40°C	136	328
cSt @ 100°C	14.5	25.3
Viscosity Index, ASTM D 2270	105	97
Pour Point, °C, ASTM D 97	-30	-18
Flash Point, °C, ASTM D 92	202	224
Density @ 15°C kg/l, ASTM D 4052	0.90	0.91

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobilube are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

