

### Product Description

Mobil DTE 20 Series are a superior range of anti-wear 'keep clean' hydraulic fluids formulated to meet ISO viscosity grade classifications 22, 32, 46, 68 and 100. They are blended from solvent refined, high viscosity index paraffinic base oils and contain a unique stabilised additive system which provides outstanding performance properties.

### Benefits

Mobil DTE 20 Series products offer the following benefits:

- Exceptional long life and 'keep clean' performance, coupled with good filterability characteristics.
- Excellent multi-metal compatibility under high temperature and/or water contamination.
- Excellent protection against rust and corrosion, wear and metal fatigue.
- Controlled demulsibility.
- Lower repair and maintenance costs due to less pump, motor and valve wear
- Improved machining accuracy and machine performance from immediate valve response.
- Increase production and high productivity at lower unit costs.
- Reduced working capital tied up in spares inventories.
- Higher operating profits.

### Applications

Mobil DTE 20 Series are recommended for hydraulic systems, pumps and motors of all designs operating under normal as well as the most severe conditions. They are particularly suited for severe modern systems where high pressures, high operating temperatures, close tolerances and fine filtration are incorporated.

### Properties

Mobil DTE 20 Oils have excellent 'keep clean' characteristics. Special stabilisers eliminate or significantly delay formation of sticky deposits or harmful degradation products which, even in minute concentrations, interfere with control valves and cause filter plugging.

Mobil DTE 20 Oils are effective with any combination of steel, cast iron, aluminium and copper alloy - and prevent corrosion under high speed heavy duty service. They protect against metal fatigue and oxidation on iron and steel under high humidity of water contaminating conditions. The oil lightly absorbs on to the metal surface and so prevents rust and surface destruction.

Mobil DTE 20 Oils have a controlled demulsibility. They will hold small amounts of water in suspension and continue to operate well. On the other hand they separate readily from large volumes of water.

## Health and Safety

Based on available toxicological information, it has been determined that this product poses no significant health risk when used and handled properly.

Details on handling, as well as health and safety information, can be found in the Material Safety Data Bulletin which can be obtained through Mobil Oil Company Ltd., by telephoning 01372 22 2000.

Typical physical characteristics are given in the table. These are intended as a guide to industry and are not necessarily manufacturing or marketing specifications.

## Product Characteristics

---

<b>Mobil DTE</b>	<b>22</b>	<b>24</b>	<b>25</b>	<b>26</b>	<b>27</b>
ISO Viscosity Grade	22	32	46	68	100
Viscosity, cSt at 40°C	22	32.0	46.0	68.0	95
Viscosity, cSt at 100°C	4.5	5.3	6.7	8.5	10.9
Viscosity Index	95	95	95	95	95
Pour Point, °C	-27	-23	-23	-23	-23
Flash Point, °C	202	202	202	204	213

---

Due to continual product research and development, the information contained herein is subject to change without notice

---

**Mobil Oil Company Limited**  
**Acting as Agent for Mobil Lubricants UK Limited**  
**ExxonMobil House, Ermyn Way**  
**Leatherhead, Surrey, KT22 8UX**  
**Telephone: 01372 22 2000**

