

Product Data Sheet

Mobil Delvac CX High Performance Diesel Engine Oil

Product Description and Application

Mobil Delvac CX is a high performance engine oil formulated from a combination of high quality mineral and hydroprocessed base oils and a superior, balanced additive system to meet the demands of modern diesel engines.

It provides excellent protection against oil thickening, high temperature engine deposits, sludge build-up, oil degradation and corrosion.

It has excellent low temperature properties which ensure ready oil circulation on start up, to prevent wear. It also has “stay in grade” shear-stability to maintain viscosity under severe, high temperature operating conditions.

Mobil Delvac CX has been especially formulated for use in fleets with a mixture of US and European diesel engines such as in bus fleets or construction/public works. It is also suitable for general petrol engine service.

Specifications

Mobil Delvac CX exceeds the requirements of:

- ACEA-98 E3
- API CG-4/SJ
- Mercedes-Benz Sheet 228.3
- Volvo VDS-2
- Cummins CES 20072
- MAN 271
- Renault VI E3R

Benefits

Mobil Delvac CX offers the following user benefits :

- Enhanced protection for diesel engines in demanding on-highway and off-highway service
- Prolonged engine life
- Excellent control of high temperature deposits
- Good soot control and dispersancy reserve
- Reduced oil consumption due to improved high temperature performance
- Extended drain compared to conventional oils

Health and Safety

Based on available toxicological information, it has been determined that this product poses no significant health risk when used and handled properly.

Details on handling, as well as health and safety information, can be found in the Material Safety Data Bulletin which can be obtained through Mobil Oil Company Ltd., by telephoning 01372 22 2000.

Typical physical characteristics are given in the table. These are intended as a guide to industry and are not necessarily manufacturing or marketing specifications.

Typical Characteristics

Mobil Delvac CX

SAE Grade	10W-40
Viscosity, cSt at 40°C	92.0
Viscosity, cSt at 100°C	14.1
Viscosity Index	148
Sulphated Ash, % wt	1.35
Total Base Number (TBN), mg KOH/g	9.8
Pour Point, °C	-30
Flash point, °C	225

Due to continual product research and development, the information contained herein is subject to change without notice.

Mobil Oil Company Limited
Acting as Agent for Mobil Lubricants UK Limited
ExxonMobil House, Ermyn Way
Leatherhead, Surrey, KT22 8UX
Telephone: 01372 22 2000

